

NCH DYNA SYSTEMS DIV -- 5014 BC-117 AEROSOL -- 6830-00F054439

=====
===== Product Identification =====

Product ID:5014 BC-117 AEROSOL
MSDS Date:02/21/1994
FSC:6830
NIIN:00F054439
MSDS Number: CFVLY
=== Responsible Party ===
Company Name:NCH DYNA SYSTEMS DIV
Address:2727 CHEMSEARCH BLVD
Box:655326
City:DALLAS
State:TX
ZIP:75265-5326
Country:US
Info Phone Num:800-336-0450/214-438-1381
Emergency Phone Num:214-438-1381/800-336-0450
Preparer's Name:L DEYOUNG
CAGE:0PH16

=== Contractor Identification ===

Company Name:NCH DYNA SYSTEMS DIV
Address:2727 CHEMSEARCH BLVD
Box:City:DALLAS
State:TX
ZIP:75265-5326
Country:US
Phone:800-336-0450/214-438-1381
CAGE:0PH16

=====
===== Composition/Information on Ingredients =====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES
MINERAL SPIRITS *97-2*
CAS:64742-88-7
Other REC Limits:100 PPM
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL (IARC-GROUP 3) *97-2*
CAS:67-63-0
RTECS #:NT8050000
Other REC Limits:400 PPM
OSHA PEL:400 PPM
ACGIH TLV:400 PPM

Ingred Name:MORPHOLINE (IARC CARCINOGEN - GROUP 3) *97-2*
CAS:110-91-8
RTECS #:QD6475000
Other REC Limits:20 PPM
OSHA PEL:70 MG/CUM (SKIN)
ACGIH TLV:71 MG/CUM (SKIN) IC

Ingred Name:ISOBUTANE, 2-METHYLPROPANE

CAS:75-28-5
RTECS #:TZ4300000
Other REC Limits:1000 PPM
OSHA PEL:1800 MG/CUM
ACGIH TLV:1000 PPM

Ingred Name:PROPANE (DIMETHYLMETHANE) *97-2*
CAS:74-98-6
RTECS #:TX2275000
Other REC Limits:1800 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:SIMPLE ASPHYXIAANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: MAY LEAD TO CNS
DEPRESSION. EYES: CAUSES EYE IRRITATION. SKIN: CAUSES DEFATTING
WHICH CAN LEAD TO IRRITATION. INGESTION: ASPIRATION MAY CAUSE
CHEMICAL PNEUMONITIS & MAY LEAD TO DEATH. MASS IVE INGESTION MAY
CAUSE LIVER & KIDNEY DAMAGE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,
UNCONSCIOUSNESS, DEFATTING

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: RINSE W/WATER. REMOVE
ANY CONTACT LENSES. FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/PLENTY
OF SOAP & WATER FOR SEVERAL MINS. INGESTION: GIVE 4 GLASSES OF
WATER. DO N'T INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS
AGAIN. OBTAIN MEDICAL ATTENTION IN ALL CASES. (SUPP)

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:110F
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER SPRAY
Fire Fighting Procedures:EVACUATE ALL UNPROTECTED PERSONNEL. WEAR
PROPER PROTECTIVE EQUIPMENT INCLUDING SCBA. COOL FIRE EXPOSED
CONTAINERS W/WATER.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY
ACCUMULATE IN LOW/INADEQUATELY VENTILATED AREAS. VAPORS MAY ALSO
TRAVEL ALONG THE GROUND & IGNITE AT DISTANT LOCATIONS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. TAKE UP
W/ABSORBENT & PLACE IN LABELED CONTAINER FOR DISPOSAL. DON'T FLUSH
TO SEWER. USE CAUTION AS SPILLS WILL BE SLIPPERY.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT MODERATE TEMPS IN A CLOSED
CONTAINER. WASH THOROUGHLY AFTER HANDLING. KEEP TEMPS BETWEEN
32-120F.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATOR WHEN EXPOSURE EXCEEDS LIMITS.

Ventilation:GENERAL EXHAUST

Protective Gloves:POLY VINYL ACETATE/EQUIVALENT

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NOTES TO PHYSICIAN: VOMITING MAY LEAD TO ASPIRATION INTO THE LUNGS WHICH MAY CAUSE DAMAGE & COULD BE FATAL.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:320F

Vapor Pres:1

Vapor Density:6

Spec Gravity:0.87

pH:9

Evaporation Rate & Reference:(BU AC=1): 0.08

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TRANSPARENT TAN W/SOLVENT ODOR

Percent Volatiles by Volume:50

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:OPEN FLAME

Hazardous Decomposition Products:CO & OXIDES OF NITROGEN

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.