

## GLENIUM 3200 HES

Version 1.3

06/28/2006

### 1. PRODUCT AND COMPANY INFORMATION

Company : **BASF Corporation**  
23700 Chagrin Blvd  
BEACHWOOD, OH 44122

Telephone : 216-839-7500

Emergency telephone number : (800) 424-9300  
(703) 527-3887 (Outside Continental US)

Product name : GLENIUM 3200 HES

MSDS ID No. : 11194

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : May contain chemicals not listed.

### 2. HAZARDOUS INGREDIENTS

Does not contain hazardous chemicals as defined by 29 CFR 1910.1200 and WHMIS.

### 3. HAZARDS IDENTIFICATION

HMIS® Rating	HEALTH	FLAMMABILITY	PHYSICAL HAZARD
	1	0	0

WHMIS Class : D2B

Primary Routes of Entry : Eye contact  
Skin contact  
Inhalation

#### Effects of Overexposure

Inhalation : Can cause slight irritation.

Skin : Can cause slight irritation.

Eyes : Can cause slight irritation.

Ingestion : Can cause slight irritation.

Chronic exposure : No known information available.

### 4. FIRST AID MEASURES

## GLENIUM 3200 HES

Version 1.3

06/28/2006

- |              |   |   |
|--------------|---|---|
| Eye contact  | : | Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.  |
| Skin contact | : | Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.  |
| Ingestion    | : | Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person. |
| Inhalation   | : | Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.  |

---

### 5. FIRE-FIGHTING MEASURES

---

- |                                  |   |  |
|----------------------------------|---|--|
| Flash point                      | : | Not combustible.   |
| Autoignition temperature         | : | no data available  |
| Lower explosion limit            | : | not applicable   |
| Upper explosion limit            | : | not applicable   |
| Suitable extinguishing media     | : | Use extinguishing agent suitable for type of surrounding fire.   |
| Fire and Explosion Hazards       | : | Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.             |
| Special Fire-fighting Procedures | : | As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear. |

---

### 6. ACCIDENTAL RELEASE MEASURES

---

- |                         |   |  |
|-------------------------|---|--|
| Methods for cleaning up | : | Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water. |
|-------------------------|---|--|

---

### 7. HANDLING AND STORAGE

---

- |         |   |                      |
|---------|---|----------------------|
| Storage | : | Keep tightly closed. |
|---------|---|----------------------|

---

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

- |                |   |  |
|----------------|---|--|
| Eye protection | : | Wear as appropriate:<br>safety glasses with side-shields<br>goggles<br>face-shield |
|----------------|---|--|

## GLENIUM 3200 HES

Version 1.3

06/28/2006

Hand protection	:	Wear as appropriate: impervious gloves
Body Protection	:	Wear as appropriate: impervious clothing preventive skin protection
Respiratory protection	:	In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
Hygienic Practices	:	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.
Engineering Controls	:	Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Color	:	brown
Physical State	:	liquid
Odor	:	characteristic
pH	:	5 - 8
Odor Threshold	:	no data available
Vapor Pressure	:	no data available
Vapor Density	:	no data available
Boiling point/range	:	ca.212 °F (100 °C)
Freeze Point	:	not applicable
Water solubility	:	completely soluble
Specific Gravity	:	1.06
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n-octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	Note: no data available

**GLENIUM 3200 HES**

Version 1.3

06/28/2006

**10. STABILITY AND REACTIVITY**

Stability : Stable under recommended storage conditions.

Conditions to avoid : Prolonged exposure to high temperatures

Materials to avoid : Strong mineral acids and oxidizing agents.

Hazardous decomposition products : Oxides of carbon

Hazardous polymerization : Will not occur under normal conditions.

**11. TOXICOLOGICAL INFORMATION**

**Acute inhalation toxicity**

<u>Product</u>	<u>Type</u> LC50	<u>Value</u> no data available	<u>Species</u>	<u>Exposure time</u>

**Acute oral toxicity**

<u>Product</u>	<u>Type</u> LD50 (Oral)	<u>Value</u> no data available	<u>Species</u>

**Acute dermal toxicity**

<u>Product</u>	<u>Type</u> LD50 (Dermal)	<u>Value</u> no data available	<u>Species</u>

**12. ECOLOGICAL INFORMATION**

Ecotoxicological Information : There is no data available for this product.

**13. DISPOSAL CONSIDERATIONS**

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

**14. TRANSPORT INFORMATION**

DOT : Proper shipping name Not regulated

IATA : Proper shipping name Not regulated

## GLENIUM 3200 HES

Version 1.3

06/28/2006

---

### 15. REGULATORY INFORMATION

---

#### SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

not applicable

#### SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

#### CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
-----------	----------------	----------------------

No CERCLA chemicals exist in this product above reportable concentrations.

#### TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

#### California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
75-21-8	ETHYLENE OXIDE
75-56-9	PROPYLENE OXIDE

---

### 16. OTHER INFORMATION

---

Legend : N.E. - Not Established  
TLV - Threshold Limit Value  
STEL - Short Term Exposure Limit  
PEL - Permissible Exposure Limit  
CEIL - Ceiling

Prepared By : Environment, Health and Safety Department



The Chemical Company

## **GLENIUM 3200 HES**

Version 1.3

06/28/2006

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.