

LAWSON PRODUCTS INC

-- 87166 FLAT BLACK ENAMEL AEROSOL PAINT

=====
MSDS Safety Information
=====

FSC: 8010
MSDS Date: 06/20/1996
MSDS Num: CCFQR
LIIN: 00F051744
Product ID: 87166 FLAT BLACK ENAMEL AEROSOL PAINT
MFN: 01
Responsible Party
Cage: 57648
Name: LAWSON PRODUCTS INC
Address: 1666 E TOUHY AVE
City: DES PLAINES IL 60018-3607
Info Phone Number: 800-323-5279/708-827-9666
Emergency Phone Number: 800-323-5279/708-827-9666
Preparer's Name: W L ANDERSON
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 57648
Name: LAWSON PRODUCTS INC
Address: UNKNOWN
City: UNKNOWN NK 00000

=====
Contractor Summary
=====

Cage: 57648
Name: LAWSON PRODUCTS INC
Address: UNKNOWN
City: UNKNOWN NK 00000
Phone: UNKNOWN

=====
Ingredients
=====

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE * 96-3 *
% Wt: 18
OSHA PEL: 2400 MG/CUM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-3*
% Wt: 18
Other REC Limits: 100 PPM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM, SKIN
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (IARC CARC- GROUP 3) *96-3*
% Wt: 10
Other REC Limits: 375 MG/CUM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE (DIMETHYLMETHANE) *96-3*
% Wt: 14
Other REC Limits: 1800 MG/CUM
OSHA PEL: 1000 PPM
ACGIH TLV: SIMPLE ASPHYXIAN

Cas: 14807-96-6
RTECS #: WW2710000
Name: TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM SILICATE *
96-3 *
% Wt: 8
OSHA PEL: 2 MG/CUM (RESP DUST)
ACGIH TLV: 2 MG/CUM (RESP DUST)

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYL BENZENE *96-3*
% Wt: 3
Other REC Limits: 100 PPM
OSHA PEL: 435 MG/CUM
ACGIH TLV: 434 MG/CUM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 106-97-8
RTECS #: EJ4200000
Name: BUTANE, N-BUTANE * 96-3 *
% Wt: 13
Other REC Limits: 800 PPM
OSHA PEL: 800 PPM
ACGIH TLV: 1900 MG/CUM

Cas: 471-34-1
RTECS #: FF9335000
Name: CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE, DURAMITE * 96-3
*
% Wt: 2
Other REC Limits: 10 MG/CUM (DUST)

RTECS #: 9999999VO
% Wt: 60.85

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: INHALATION: MAY CAUSE NARCOSIS IN HIGH VAPOR
CONCENTRATIONS. EFFECTS ARE REVERSIBLE. LONG TERM EXPOSURE (YEARS) MAY
CAUSE

LUNG, LIVER/KIDNEY DAMAGE. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY
CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. MAY AFFECT THE EYES.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: DIFFICULTY IN BREATHING, REDNESS,
VOMITING, DIZZINESS, NARCOSIS, DEFATTING OF SKIN

First Aid: INHALATION: GIVE OXYGEN. INGESTION: DON'T INDUCE VOMITING. GASTRIC
LAVAGE. EYES/SKIN: WASH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Handling and Disposal
=====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES, VENTILATE. AVOID
BREATHING VAPORS & REMOVE W/INERT ABSORBENT.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL
REGULATIONS. DON'T PUNCTURE/INCINERATE CONTAINER. DON'T REUSE CONTAINER.
WRAP

CONTAINER & PLACE IN TRASH COLLECTION.

Handling And Storage Precautions: DON'T STORE IN TEMPERATURES >120F.

Other Precautions: READ & FOLLOW CONTENTS ON PRODUCT LABEL. TREAT AS
CYLINDER OF COMPRESSED GAS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: 0F

Lower Limits: 1

Upper Limits: 12.8

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: USE SELF CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING WHEN FIGHTING FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard: DON'T SPRAY NEAR OPEN FLAME. KEEP AT ROOM
TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT/OTHER HEAT MAY CAUSE BURSTING.

=====
Control Measures
=====

Respiratory Protection: IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED
EXPOSURE

LIMITS, A SUITABLE NIOSH RESPIRATOR SHOULD BE WORN.

Ventilation: IF VENTILATION ISN'T ADEQUATE IN MAINTAINING AIRBORNE
CONCENTRATION < EXPOSURE LIMITS, EXHAUST SYSTEMS MAY BE REQUIRED.

Protective Gloves: REQUIRED FOR PROLONGED/REPEATED CONTACT

Eye Protection: SAFETY GLASSES

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWERS

Work Hygienic Practices: WASH HANDS BEFORE EATING/USING THE WASHROOM. SMOKE
IN

SMOKING AREAS ONLY.

=====
Physical/Chemical Properties
=====

B.P. Text: 0F

Evaporation Rate & Reference: FASTER THAN ETHER

Appearance and Odor: BLACK COLOR W/SOLVENT ODOR

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: OPEN FLAME, DIRECT SUNLIGHT/OTHER HEAT SOURCES,
TEMPS >120F
Hazardous Decomposition Products: BY OPEN FLAME: CO, CO2
Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====

Product ID: 87166 FLAT BLACK ENAMEL AEROSOL PAINT
Cage: 57648
Company Name: LAWSON PRODUCTS INC
Street: UNKNOWN
City: UNKNOWN NK
Zipcode: 00000
Health Emergency Phone: 800-323-5279/708-827-9666
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: INHALATION: MAY CAUSE NARCOSIS IN HIGH VAPOR
CONCENTRATIONS. EFFECTS ARE REVERSIBLE. LONG TERM EXPOSURE (YEARS) MAY
CAUSE
LUNG, LIVER/KIDNEY DAMAGE. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY
CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. MAY AFFECT THE EYES.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use
or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the
United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of
the
United States of America should seek competent professional advice to
verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.