

LAWSON PRODUCTS INC

-- 87168 GLOSS WHITE AEROSOL PAINT

=====
MSDS Safety Information
=====

FSC: 8010
MSDS Date: 03/06/1995
MSDS Num: CCFQS
LIIN: 00F051745
Product ID: 87168 GLOSS WHITE AEROSOL PAINT
MFN: 01
Responsible Party
Cage: 57648
Name: LAWSON PRODUCTS INC
Address: 1666 E TOUHY AVE
City: DES PLAINES IL 60018-3607
Info Phone Number: 800-323-5279/708-827-9666
Emergency Phone Number: 800-323-5279/708-827-9666
Preparer's Name: W L ANDERSON
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 57648
Name: LAWSON PRODUCTS INC
Address: UNKNOWN
City: UNKNOWN NK 00000

=====
Contractor Summary
=====

Cage: 57648
Name: LAWSON PRODUCTS INC
Address: UNKNOWN
City: UNKNOWN NK 00000
Phone: UNKNOWN

=====
Ingredients
=====

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *96-3*
% Wt: 14
Other REC Limits: 100 PPM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM, SKIN
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 13463-67-7
RTECS #: XR2275000
Name: TITANIUM DIOXIDE, TITANIUM OXIDE (SUSPECTED ANIMAL CARCINOGEN, IARC
GROUP 3) *96-3*
% Wt: 9
OSHA PEL: 15 MG/CUM
ACGIH TLV: 10 MG/CUM (DUST)

Cas: 74-98-6

RTECS #: TX2275000
Name: PROPANE (DIMETHYLMETHANE) *96-3*
% Wt: 15
Other REC Limits: 1800 MG/CUM
OSHA PEL: 1000 PPM
ACGIH TLV: SIMPLE ASPHYXIAN

Cas: 106-97-8
RTECS #: EJ4200000
Name: BUTANE, N-BUTANE * 96-3 *
% Wt: 14
Other REC Limits: 800 PPM
OSHA PEL: 800 PPM
ACGIH TLV: 1900 MG/CUM

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (IARC CARC- GROUP 3) *96-3*
% Wt: 5
Other REC Limits: 375 MG/CUM
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE * 96-3 *
% Wt: 23
OSHA PEL: 2400 MG/CUM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 763-69-9
RTECS #: UF3325000
Name: ETHYL 3-ETHOXYPROPIONATE, PROPANOIC ACID, 3-ETHOXY-, ETHYL ESTER
96-3
% Wt: 5

Cas: 100-41-4
RTECS #: DA0700000
Name: ETHYL BENZENE *96-3*
% Wt: 3
Other REC Limits: 100 PPM
OSHA PEL: 435 MG/CUM
ACGIH TLV: 434 MG/CUM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

RTECS #: 9999999VO
% Wt: 79.36

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES

Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: INHALATION: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. MAY CAUSE IRRITATION TO SKIN & UPPER RESPIRATORY SYSTEM. INGESTION: HARMFUL/FATAL. MAY AFFECT THE LUNGS, CNS & EYES. REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: IRRITATION, LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS, NAUSEA

First Aid: INHALATION: GIVE OXYGEN. INGESTION: DON'T INDUCE VOMITING. GASTRIC LAVAGE. EYES/SKIN: WASH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Handling and Disposal
=====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES, VENTILATE. AVOID BREATHING VAPORS & REMOVE W/INERT ABSORBENT.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T PUNCTURE/INCINERATE CONTAINER.

Handling And Storage Precautions: DON'T STORE IN TEMPERATURES >120F.

Other Precautions: READ & FOLLOW CONTENTS ON PRODUCT LABEL. TREAT AS CYLINDER OF COMPRESSED GAS.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TOC

Flash Point Text: 0F

Lower Limits: 1

Upper Limits: 12.8

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: WATER SPRAY MAY BE USED TO MINIMIZE VAPORS/COOL CONTAINERS. AVOID SPREADING BURNING LIQUID W/WATER USED FOR COOLING. MOVE UNDAMAGED CONTAINERS SAFELY W/O RISK.

Unusual Fire/Explosion Hazard: DON'T SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT/OTHER HEAT MAY CAUSE BURSTING. PRESSURIZED CONTAINERS MAY RUPTURE >120F.

=====
Control Measures
=====

Respiratory Protection: IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE

LIMITS, A SUITABLE NIOSH RESPIRATOR SHOULD BE WORN.

Ventilation: IF VENTILATION ISN'T ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATION < EXPOSURE LIMITS, EXHAUST SYSTEMS MAY BE REQUIRED.

Protective Gloves: REQUIRED FOR PROLONGED/REPEATED CONTACT

Eye Protection: SAFETY EYEWEAR W/SPLASH GUARDS

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWERS

Work Hygienic Practices: WASH HANDS BEFORE EATING/USING THE WASHROOM. SMOKE IN SMOKING AREAS ONLY.

=====
Physical/Chemical Properties
=====

B.P. Text: -99F

Vapor Density: >1
Evaporation Rate & Reference: FASTER THAN ETHER
Appearance and Odor: WHITE COLOR W/SOLVENT ODOR
Percent Volatiles by Volume: 90

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: HEAT, OPEN FLAME, DIRECT SUNLIGHT, TEMPS >120F
Hazardous Decomposition Products: BY OPEN FLAME: CO, CO2
Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

HAZCOM Label
=====

Product ID: 87168 GLOSS WHITE AEROSOL PAINT
Cage: 57648
Company Name: LAWSON PRODUCTS INC
Street: UNKNOWN
City: UNKNOWN NK
Zipcode: 00000
Health Emergency Phone: 800-323-5279/708-827-9666
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A

Origination Code: G

Hazard And Precautions: INHALATION: IN A CONFINED AREA VAPORS IN HIGH
CONCENTRATION ARE ANESTHETIC. MAY CAUSE IRRITATION TO SKIN & UPPER
RESPIRATORY SYSTEM. INGESTION: HARMFUL/FATAL. MAY AFFECT THE LUNGS, CNS &
EYES. REPEATE D/PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT
BRAIN
& NERVOUS SYSTEM DAMAGE.
=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use
or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the
United
States of America and disclaims all liability for such use. Any person

utilizing this instruction who is not a military or civilian employee of the

United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.