



Revision Date: 03/14/2007

Issue date: 03/14/2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite(R) Superflex(R) Clear RTV Silicone Adhesive Sealant
Product type: Silicone
Company address: Henkel Corporation, 1001 Trout Brook Crossing, Rocky Hill, Connecticut 06067
Item No.: 59530
Region: United States
Contact Information: Telephone: 860.571.5100, Emergency telephone: 860.571.5100, Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Table with 5 columns: Hazardous components, %, ACGIH TLV, OSHA PEL, OTHER. Rows include Distillates(petroleum), hydrotreated middle, Silica, amorphous (fumed), Ethyltriacetoxysilane, Methyltriacetoxysilane, and Acetic acid.

Non hazardous components
Silicone Resins 50-100 %

The above components are hazardous as defined in 29 CFR 1910.1200. Exposure to moisture during cure will release 1-5% acetic acid.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:
Physical state: Paste
Color: Translucent
Odor: Acetic Acid
HEALTH: 2
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin contact, Eye contact, Inhalation

Potential Health Effects

Inhalation: Acetic acid produced during cure may irritate eyes, nose and throat. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.

Item No.: 59530

Product name: Loctite(R) Superflex(R) Clear RTV Silicone Adhesive Sealant

Skin contact: May cause skin irritation.
Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.

Ingestion: Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Acetic acid: 4%

Flammable/Explosive limits-upper %: Acetic acid: 19.9% @ 200°F

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

Hazardous combustion products: Formaldehyde. Silica Mist. Acrid smoke and fumes.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Scrape up as much material as possible. Spilled material will solidify. Store in a closed container until ready for disposal. Maintain good ventilation for large spills.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.

Storage: Store in a dry area below 90° F Keep container closed.

Incompatible products: Acids. Oxidizing agents. Avoid contact with water.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

Item No. : 59530

Product name: Loctite(R) Superflex(R) Clear RTV Silicone Adhesive Sealant
2 of 5

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Ensure adequate ventilation, especially in confined areas.
Respiratory protection:	No personal respiratory protective equipment normally required. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Skin protection:	Chemical resistant, impermeable gloves.
Eye/face protection:	Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Translucent
Odor:	Acetic Acid
Vapor pressure:	<10 mmHg @20°C (68° F)
pH:	Not applicable
Boiling point/range:	Not available
Melting point/range:	Not available
Specific gravity:	1.01 at 20 deg. C
Vapor density:	Heavier than air
Evaporation rate:	Not available
Solubility in water:	Insoluble. Polymerizes in presence of water
Partition coefficient (n-octanol/water):	Not available
VOC content:	3.08%; 32 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Acetic acid is liberated slowly upon contact with moisture. Formaldehyde.
Incompatibility:	Acids. Bases. Oxidizing agents. Water.
Conditions to avoid:	Prolonged heating at temperatures above 150 °C. Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Distillates(petroleum), hydrotreated middle 64742-46-7	No	No	No
Silica, amorphous (fumed) 7631-86-9	No	No	No
Ethyltriacetoxysilane 17689-77-9	No	No	No
Methyltriacetoxysilane 4253-34-3	No	No	No
Acetic acid 64-19-7	No	No	No

Literature Referenced Target Organ & Other Health Effects

Item No. : 59530

Product name: Loctite(R) Superflex(R) Clear RTV Silicone Adhesive Sealant

3 of 5

Hazardous components	Health Effects/Target Organs
Distillates(petroleum), hydrotreated middle 64742-46-7	Irritant
Silica, amorphous (fumed) 7631-86-9	Nuisance dust
Ethyltriacetoxysilane 17689-77-9	No Target Organs
Methyltriacetoxysilane 4253-34-3	Allergen, Irritant
Acetic acid 64-19-7	Kidney, Irritant, Immune system, Gastrointestinal, Eyes, Corrosive, Allergen

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose according to EPA and local governmental regulations. Cured rubber can be incinerated or landfilled following EPA and local regulations.

EPA hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None known

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None above reporting de minimus.
CERCLA/SARA Section 311/312: Immediate Health Hazard
CERCLA/SARA 313: None above reporting de minimus.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 3, 15

Prepared by: Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.